

Battery operated lifting aids

ezzLIFTmaster80

ezzLIFTmaster is a high-quality, battery-operated mobile lifting aid, available in steel and stainless steel. The ezzLIFTmaster80 is the perfect combination of ergonomics, safety and functional design. The versatile standardized accessories and the customer-specific solutions offer an attractive aid for many work processes involving lifting and moving. Thanks to the design and the high-quality materials, it can be used in many ways and is also easy to clean.



Details:

- High-performance lifter
- Drive with ball screw spindle for high safety and precision
- Low maintenance
- Braked motor
- 100 mm / sec lifting speed
- Remote control device with spiral cable
- Rear castors with foot brakes
- Versatility through quick-change coupling
- ... and much more

Lifting height:












- 2000 mm
- 2200 mm
- Special heights up to 2500 mm

Load capacity: 80 kg





Equipment:

 <p>Roll turner Roll handling tool: Pick up in the core and turn in horizontal and vertical position</p> <p>Ø Rolls: max. 650 mm roll width: max. 500 mm max. weight: 45 kg core from 70-76 mm or 152 mm</p>	 <p>Fork Horizontal support for rollers</p> <p>max. weight: 80 kg</p>	
 <p>Tool lift with hook Tools, hoists and hooks can be individually adapted</p> <p>max. weight: 80 kg</p>	 <p>Front loader for rollers Tool for inserting rolls into machines</p> <p>max. weight: 80 kg</p>	
 <p>Rotatable V-block Tool for transporting and positioning rolls, e.g. on packaging machines</p> <p>max. weight: 80 kg</p>	 <p>Platform Equipped with a standard plastic platform for loading and unloading</p> <p>max. weight: 80 kg</p>	
 <p>Gripper Unit for gripping and rotating rolls and containers of different geometries</p> <p>max. weight: 80 kg</p>	 <p>KLT-fork For gripping load carriers</p> <p>distance adjustable max. weight: 80 kg Customizable fork</p>	
 <p>Pallet wheel – Ø 60 mm pallet-compatible</p>	 <p>Swivel caster – Ø 75 mm</p>	 <p>Swivel caster – Ø 60 mm pallet-compatible</p>

