

Battery operated lifting aids

ezzLIFTmaster300

ezzLIFTmaster is a high-quality, battery-operated mobile lifting aid, available in steel and stainless steel. The ezzLIFTmaster300 is the perfect combination of ergonomics, safety and functional design. The versatile standardized accessories and the customer-specific solutions offer an attractive aid for many work processes involving lifting and moving. Thanks to its design and high-quality materials, ezzLIFTmaster300 can be used in a variety of ways and is also easy to clean.



Details:


- High-performance lifter
- Drive with ball screw spindle for high safety and precision
- Low maintenance
- Braked motor
- 65 mm / sec lifting speed
- Remote control device with spiral cable
- Rear castors with foot brakes
- Versatility through quick-change coupling
- ... and much more

Height:

- 2000 mm
- 2200 mm
- Special heights up to 2500 mm

Load capacity: 300 kg

ATEX solution available





Equipment:

 <p>Spike For holding and storing all kinds of rolls</p> <p>max. weight: 300 kg</p>	 <p>Fork Horizontal support for rollers</p> <p>max. weight: 300 kg</p>	
 <p>Tool lift Ideal for large thermoforming tools and many other tools, hoists and hooks, individually adaptable</p> <p>max. weight: 300 kg</p>	 <p>Roll turner For handling rolls: picking up in the core and turning in horizontal and vertical position (manually or electrically operated)</p> <p>max. roll width 620 mm max. \varnothing roll: 700 mm max. weight: 250 kg core of 70-76 or 152 mm</p>	
 <p>Rotatable V-block Tool for transporting and positioning rolls, e.g. on packaging machines</p> <p>max. weight: 300 kg</p>	 <p>Platform Equipped with a standard plastic platform for loading and unloading. Alternatively, platform made of stainless steel</p> <p>max. weight: 300 kg</p>	
 <p>Gripper Unit for gripping and rotating containers of different geometries</p> <p>max. weight: : 300 kg</p>	 <p>KLT-fork For gripping load carriers</p> <p>distance adjustable max. weight: 300 kg customizable fork</p>	
 <p>Pallet wheel – \varnothing 80 mm pallet-compatible</p>	 <p>Swivel caster – \varnothing 60 mm</p>	 <p>Duplex pallet wheel – \varnothing 82 mm pallet-compatible</p>

